



US005719107A

[11] Patent Number: 5,719,107

[45] Date of Patent: Feb. 17, 1998

0 317 354 5/1989 European Pat. Off. .
WO 92/18588 10/1992 WIPO .

OTHER PUBLICATIONS

PCT Search Report date Sep. 5, 1995.

Mack Truck Technical Services Standard Test Procedure No. 5GT 57 "Mack T-7: Diesel Engine Oil Viscosity Evaluation", Aug. 31, 1984 (Mack T-7).

Mack Truck Technical Services Standard Test Procedure No. 5GT 76 "Mack T-8: Diesel Engine Oil Viscosity Evaluation", Oct. 1993 (Mack T-8).

"Corrosion in Lubricant Systems", Dr. Tony Smith, M.Sc., Anti-Corrosion, Nov. 1983, pp. 15-16.

"Corrosion of Copper and Lead Containing Materials by Diesel Lubricants", C. M. Cusano and J. C. Wang, Cummins Engine Company, Journal of the Society of Tribologists and Lubrication Engineers, Lubrication Engineering, vol. 51, 1, pp. 89-95 Date unavailable.

"The Function of Lube-Oil in Fighting Corrosion in Medium-Speed Engines", P. R. Belcher, Bsc, CEng, Shell International Petroleum Co. Ltd., Lubrication Engineering, Feb. 1993, pp. 145-150.

"Protective Automotive Lubricants", András Zakar, Hungarian Hydrocarbon Institute, Journal of the Society of Tribologists and Lubrication Engineers, vol. 49, 2, pp. 145-150 date unavailable.

Primary Examiner—Jacqueline V. Howard
Attorney, Agent, or Firm—E. C. Bakun

[57] ABSTRACT

Thus, the instant invention is directed toward an oil for diesel engines comprising an admixture of (A) a major amount of an oil of lubricating viscosity, (B) at least 4 mass % dispersant, (C) at least 0.3 mass % of a metal phenate, (D) less than 0.1 mass % friction modifier, (E) less than 0.3 mass % of ashless sulfurized phenols and, (F) less than 0.12 mass % neutral calcium sulfonate.

14 Claims, No Drawings